



FLEXTRED™ S1PS SAFETY BOOTS BLACK B1M110133 SC FO SR ESD



ENERGY FOAM



**ROLLCAGE™
stabilizer**



STEP-RELEASE™



BOA® Fit System



PS
Non-metallic perforation-resistant inserts and insoles



FO
Resistance to fuel oil



SR
Slip resistance on ceramic tile floor with glycerine

FEATURES

- Flexible and lightweight all-round safety boots for tradesmen protection.
- ENERGY FOAM heel cushioning construction for superior energy return and maximum comfort.
- STEP-RELEASE™ heel for a convenient and rapid shoe removal.
- ROLLCAGE™ heel stabilizer for great stability even in demanding terrain.
- BOA® Fit System delivers micro adjustable precision fit, engineered to perform in the toughest conditions.
- Textile upper for all-day ventilation and breathability.
- Reinforced front to protect toe cap from abrasion.
- Metal free construction, except BOA® Fit System which still allows users to conveniently pass through security gates.
- Superior grip to prevent slipping.
- ESD (electrostatic discharge) certified.
- Certified according to EN ISO 20345:2022+A1:2024 S1PS SC FO SR ESD.
- Available sizes: 36-48.

Disclaimer

Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH

71364 Winnenden
Germany

www.milwaukeetool.eu

**STAY SAFE.
STAY PRODUCTIVE.**





FLEXTRED™ S1PS SAFETY BOOTS BLACK B1M110133 SC FO SR ESD



TECHNICAL INFORMATION

Article number 4932498093

Shoe type Mid cut

Metal free No

Shoe size (EU/UK) 36/3

Packaging style Carton box

Packaging (inner/master) 1/10

USAGE INSTRUCTIONS

The shoes shall only be used as safety shoes. Using the shoes beyond this application area is not permissible. Depending on the version, the shoes shall be protected against such risks as moisture, impacts in the toe area (impact and pressure forces), perforation of foreign objects through the sole, slipping, electric properties, light cuts on the boot shaft sides, heat and cold.

STORAGE INSTRUCTIONS

Regular maintenance of safety shoes is essential to ensure their continued effectiveness. Clean shoes regularly using a soft brush and mild soap. Avoid using harsh chemicals or solvents as they may damage the shoes. Inspect shoes regularly for any signs of damage or wear and replace if necessary. Store safety shoes in original package in a dry, cool place, away from direct sunlight or heat sources. Avoid storing shoes in damp or humid conditions, as this may cause damage or deterioration. Do not store shoes in areas where they may be exposed to chemicals or other hazardous substances.

PERIOD OF OBSOLESCENCE

It is not recommended to store the product for more than 5 years. It is recommended to replace safety shoes every 12 months, or sooner if they become damaged or worn.

Disclaimer

Information present within this sheet was correct at the date of issue.

Techtronic Industries GmbH

71364 Winnenden
Germany

www.milwaukeetool.eu

**STAY SAFE.
STAY PRODUCTIVE.** 